

ISLAMIC UNIVERSITY OF TECHNOLOGY (IUT)
ORGANISATION OF ISLAMIC COOPERATION (OIC)
DEPARTMENT OF CIVIL AND ENVIRONMENTAL ENGINEERING

Mid Semester Examination
Course Number: CEE 4713
Course Title: Design of Steel Structures

Winter Semester: 2022–2023
Full Marks: 75
Time: 1.5 Hours

There are 3 (three) questions. Answer all questions. The figures in the right margin indicate full marks. COs and POs are also specified in the right margin of the questions. The symbols have their usual meaning.

1. (a) Explain the process of residual stress development in rolled flat bar with schematic diagrams. (CO1) (5)
(PO1)
- (b) Investigate the tension capacity of the plate PL $12 \times \frac{5}{8}$ attached to the gusset plate with 11 bolts shown in Fig. 1. The material is A36 ($F_y = 36$ ksi, $F_u = 58$ ksi). Bolt are $\frac{3}{4}$ inch diameter with standard holes. Use LRFD method. (CO2) (15)
(PO2)




Fig.1 for Question 1 (b)

2. (a) Explain the considerations we assume for the design of structures. (CO1) (5)
(PO1)
- (b) Calculate the flexural strength of a W 14 × 68 of A 572 Grade 50 steel subjected to (CO2) (15)
(PO2)
- I. Continuous lateral support
 - II. An unbraced length of 20ft with $C_b = 1.0$
 - III. An unbraced length of 30ft with $C_b = 1.0$

- (c) Design the beam shown in Fig.2 using the lightest W section with A 992 steel ($F_y = 50$ ksi) to achieve full plastic moment capacity. (CO3) (7.5)
(PO3)




Fig.2 for Question 2 (c)

3. (a) Explain the assumptions that are considered for an ideal column. (CO1) (5)
(PO1)
(b) Calculate the effective length factor K_s for the columns AB and BC of the rigid frame shown in Fig. 3. Each member is oriented so that its web is in the plane of the frame. (CO2) (7.5)
(PO2)




Fig.3 for Question 3 (b)

- (c) Design a column with an effective length $L_c = 26$ feet and which has to resist a service dead load of 100 kips and a service live load of 300 kips. Select a W18 shape with $F_y = 70$ ksi. Use ASD Method. (CO3) (15)
(PO3)

Element	λ	λ_p	λ_r
Flange	$\frac{b_f}{2t_f}$	$0.38 \sqrt{\frac{E}{F_y}}$	$1.0 \sqrt{\frac{E}{F_y}}$
Web	$\frac{h}{t_w}$	$3.76 \sqrt{\frac{E}{F_y}}$	$5.70 \sqrt{\frac{E}{F_y}}$

*For hot-rolled I shapes in flexure.

SUMMARY OF MOMENT STRENGTH

The procedure for computation of nominal moment strength for I and C-shaped sections bent about the x axis will now be summarized. All terms in the following equations have been previously defined, and AISC equation numbers will not be shown.

This summary is for compact and noncompact shapes (noncompact flange) only (no slender shapes).

- Determine whether the shape is compact.
- If the shape is compact, check for lateral-torsional buckling as follows.

If $L_b \leq L_p$, there is no LTB, and $M_n = M_p$.

If $L_p < L_b \leq L_r$, there is inelastic LTB, and

$$M_n = C_b \left[M_p - (M_p - 0.7F_y S_x) \left(\frac{L_b - L_p}{L_r - L_p} \right) \right] \leq M_p$$

If $L_b > L_r$, there is elastic LTB, and

$$M_n = F_{cr} S_x \leq M_p$$

where

$$F_{cr} = \frac{C_b \pi^2 E}{(L_b/r)^2} \sqrt{1 + 0.078 \frac{Jc}{S_x \lambda_c^2 (r_x)^2}}$$

- If the shape is noncompact because of the flange, the axial strength will be the smaller of the strengths corresponding to flange local buckling and lateral-torsional buckling.

a. Flange local buckling:

If $\lambda > \lambda_{nc}$, there is no FLD

If $\lambda_p < \lambda \leq \lambda_{nc}$, the flange is noncompact, and

$$M_n = M_p - (M_p - 0.7F_y S_x) \left(\frac{\lambda - \lambda_p}{\lambda_{nc} - \lambda_p} \right)$$

b. Lateral-torsional buckling:

If $L_b \leq L_p$, there is no LTB

If $L_p < L_b \leq L_r$, there is inelastic LTB, and

$$M_n = C_b \left[M_p - (M_p - 0.7F_y S_x) \left(\frac{L_b - L_p}{L_r - L_p} \right) \right] \leq M_p$$

If $L_b > L_r$, there is elastic LTB, and

$$M_n = F_{cr} S_x \leq M_p$$

where

$$F_{cr} = \frac{C_b \pi^2 E}{(L_b/r)^2} \sqrt{1 + 0.078 \frac{Jc}{S_x \lambda_c^2 (r_x)^2}}$$

LATERAL BRACING REQUIREMENT

Unbraced length L_b to achieve just M_p (elastic LTB of compact sections) (Case-2)

$$\frac{L_b}{r_x} = 1.76 \sqrt{\frac{E}{F_y}} = \frac{300}{\sqrt{F_y, ksi}} \quad (9.5.5)$$

Unbraced length L_b to achieve $M_n = 0.7F_y S_x$ (LTB of compact sections) (Case-3).

$$L_b = 1.95 \sqrt{\frac{E}{0.7F_y} \frac{Jc}{S_x \lambda_c^2} \sqrt{1 + \sqrt{1 + 6.76 \left(\frac{0.7F_y S_x \rho_x}{E} \right)^2}}} \quad (9.6.6)$$

$$\text{where } r_x^2 = \frac{\sqrt{I_x c}}{S_x}$$

$c = 1$ for a doubly symmetric I-shape

$c = \frac{h_x}{2} \sqrt{\frac{I_x}{I_y}}$ for a channel

h_x = distance between the flange centroids, in.

Approximately

$$r_x = \frac{b_f}{\sqrt{12 \left(1 + \frac{1}{6} \frac{A_w}{b_f t_f} \right)}}$$

$$4.71 \sqrt{\frac{E}{F_y}}$$

To summarize,


$$\text{When } \frac{L_b}{r_x} \leq 4.71 \sqrt{\frac{E}{F_y}},$$

$$F_{cr} = (0.658^{F_y/E}) F_y$$

$$F_e = \frac{P_e}{A} = \frac{\pi^2 E}{(L_c/r)^2}$$

$$\text{When } \frac{L_b}{r_x} > 4.71 \sqrt{\frac{E}{F_y}},$$

$$F_{cr} = 0.877 F_e$$



Stiffness modification factors for beams:

Condition	Sidesway (unbraced)	No sidesway (braced)
Far end of beam hinged	0.5	1.5
Far end of beam fixed	0.667	2.0




Table 1-1 (continued)
W-Shapes
Dimensions


Shape	Area, A	Depth, d	Thickness, t_w	Web Thickness, t_f	Flange Width, b_f	Thickness, t_f		Flange Radius, R		Distance		
						t_f	t_f	R_{top}	R_{bot}	A	F	
	in^2	in	in	in	in	in	in	in	in	in	in	
W6x30	33.9	18.0	1.02	1/8	13.7	12 5/8	2.72	2/8	3.22	2/8	37 3/8	29 3/8
W6x27	30.7	17.0	1.02	1/8	12 1/2	12 1/8	2.68	2/8	2.98	2/8	37 1/8	29 1/8
W6x25	28.7	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	2.78	2/8	37 1/8	29 1/8
W6x20	26.7	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	2.78	2/8	37 1/8	29 1/8
W6x18	25.0	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	2.58	2/8	37 1/8	29 1/8
W6x16	23.7	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	2.38	2/8	37 1/8	29 1/8
W6x15	23.0	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	2.18	2/8	37 1/8	29 1/8
W6x14	22.8	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	1.98	2/8	37 1/8	29 1/8
W6x12	21.6	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	1.78	2/8	37 1/8	29 1/8
W6x10	20.3	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	1.58	2/8	37 1/8	29 1/8
W6x9	19.2	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	1.38	2/8	37 1/8	29 1/8
W6x8	18.2	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	1.18	2/8	37 1/8	29 1/8
W6x6	16.7	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	0.98	2/8	37 1/8	29 1/8
W6x4	14.7	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	0.78	2/8	37 1/8	29 1/8
W6x3	14.0	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	0.58	2/8	37 1/8	29 1/8
W6x2	13.3	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	0.38	2/8	37 1/8	29 1/8
W6x1	12.6	17 1/2	1.00	1/8	12 1/2	12 1/8	2.68	2/8	0.18	2/8	37 1/8	29 1/8
W8x31	36.3	20.0	1.14	1/8	14.5	14 1/8	3.00	3/8	3.50	3/8	43 1/8	35 1/8
W8x28	33.1	19.0	1.14	1/8	14.5	14 1/8	3.00	3/8	3.30	3/8	43 1/8	35 1/8
W8x26	31.2	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	3.10	3/8	43 1/8	35 1/8
W8x24	29.4	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	2.90	3/8	43 1/8	35 1/8
W8x22	27.7	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	2.70	3/8	43 1/8	35 1/8
W8x20	26.1	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	2.50	3/8	43 1/8	35 1/8
W8x18	24.6	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	2.30	3/8	43 1/8	35 1/8
W8x16	23.1	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	2.10	3/8	43 1/8	35 1/8
W8x14	21.6	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	1.90	3/8	43 1/8	35 1/8
W8x12	20.3	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	1.70	3/8	43 1/8	35 1/8
W8x10	19.1	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	1.50	3/8	43 1/8	35 1/8
W8x8	18.0	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	1.30	3/8	43 1/8	35 1/8
W8x6	17.0	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	1.10	3/8	43 1/8	35 1/8
W8x4	16.1	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	0.90	3/8	43 1/8	35 1/8
W8x3	15.3	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	0.70	3/8	43 1/8	35 1/8
W8x2	14.6	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	0.50	3/8	43 1/8	35 1/8
W8x1	14.0	19 1/2	1.14	1/8	14.5	14 1/8	3.00	3/8	0.30	3/8	43 1/8	35 1/8
W10x39	39.8	21.0	1.31	1/8	16.5	16 1/8	3.50	3/8	4.00	3/8	49 1/8	41 1/8
W10x36	36.8	20.0	1.31	1/8	16.5	16 1/8	3.50	3/8	3.80	3/8	49 1/8	41 1/8
W10x33	34.0	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	3.60	3/8	49 1/8	41 1/8
W10x30	31.3	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	3.40	3/8	49 1/8	41 1/8
W10x28	29.7	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	3.20	3/8	49 1/8	41 1/8
W10x26	28.2	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	3.00	3/8	49 1/8	41 1/8
W10x24	26.7	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	2.80	3/8	49 1/8	41 1/8
W10x22	25.3	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	2.60	3/8	49 1/8	41 1/8
W10x20	24.0	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	2.40	3/8	49 1/8	41 1/8
W10x18	22.8	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	2.20	3/8	49 1/8	41 1/8
W10x16	21.6	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	2.00	3/8	49 1/8	41 1/8
W10x14	20.5	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	1.80	3/8	49 1/8	41 1/8
W10x12	19.5	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	1.60	3/8	49 1/8	41 1/8
W10x10	18.6	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	1.40	3/8	49 1/8	41 1/8
W10x8	17.8	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	1.20	3/8	49 1/8	41 1/8
W10x6	17.0	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	1.00	3/8	49 1/8	41 1/8
W10x4	16.3	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	0.80	3/8	49 1/8	41 1/8
W10x3	15.7	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	0.60	3/8	49 1/8	41 1/8
W10x2	15.2	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	0.40	3/8	49 1/8	41 1/8
W10x1	14.7	19 1/2	1.31	1/8	16.5	16 1/8	3.50	3/8	0.20	3/8	49 1/8	41 1/8
W12x50	50.0	23.0	1.59	1/8	19.0	19 1/8	4.00	3/8	4.50	3/8	57 1/8	49 1/8
W12x46	46.7	22.0	1.59	1/8	19.0	19 1/8	4.00	3/8	4.30	3/8	57 1/8	49 1/8
W12x42	43.5	21.0	1.59	1/8	19.0	19 1/8	4.00	3/8	4.10	3/8	57 1/8	49 1/8
W12x38	40.3	20.0	1.59	1/8	19.0	19 1/8	4.00	3/8	3.90	3/8	57 1/8	49 1/8
W12x34	37.1	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	3.70	3/8	57 1/8	49 1/8
W12x30	34.0	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	3.50	3/8	57 1/8	49 1/8
W12x28	32.6	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	3.30	3/8	57 1/8	49 1/8
W12x26	31.2	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	3.10	3/8	57 1/8	49 1/8
W12x24	29.9	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	2.90	3/8	57 1/8	49 1/8
W12x22	28.7	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	2.70	3/8	57 1/8	49 1/8
W12x20	27.6	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	2.50	3/8	57 1/8	49 1/8
W12x18	26.6	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	2.30	3/8	57 1/8	49 1/8
W12x16	25.7	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	2.10	3/8	57 1/8	49 1/8
W12x14	24.9	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	1.90	3/8	57 1/8	49 1/8
W12x12	24.2	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	1.70	3/8	57 1/8	49 1/8
W12x10	23.6	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	1.50	3/8	57 1/8	49 1/8
W12x8	23.1	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	1.30	3/8	57 1/8	49 1/8
W12x6	22.7	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	1.10	3/8	57 1/8	49 1/8
W12x4	22.4	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	0.90	3/8	57 1/8	49 1/8
W12x3	22.1	19 1/2	1.59	1/8	19.0	19 1/8	4.00	3/8	0.70	3/8	57 1/8	49 1/8
W14x70	70.0	27.0	1.94	1/8	22.0	22 1/8	4.50	3/8	5.00	3/8	65 1/8	57 1/8
W14x66	66.5	26.0	1.94	1/8	22.0	22 1/8	4.50	3/8	4.80	3/8	65 1/8	57 1/8
W14x62	63.1	25.0	1.94	1/8	22.0	22 1/8	4.50	3/8	4.60	3/8	65 1/8	57 1/8
W14x58	59.7	24.0	1.94	1/8	22.0	22 1/8	4.50	3/8	4.40	3/8	65 1/8	57 1/8
W14x54	56.4	23.0	1.94	1/8	22.0	22 1/8	4.50	3/8	4.20	3/8	65 1/8	57 1/8
W14x50	53.2	22.0	1.94	1/8	22.0	22 1/8	4.50	3/8	4.00	3/8	65 1/8	57 1/8
W14x46	50.1	21.0	1.94	1/8	22.0	22 1/8	4.50	3/8	3.80	3/8	65 1/8	57 1/8
W14x42	47.1	20.0	1.94	1/8	22.0	22 1/8	4.50	3/				



**Table 1-1 (continued)
W-Shapes
Dimensions**

Shape	Area, in. ²	Depth, in.	WEO		Flange		Thickness		F		Distance		Weld- able depth range, in.
			d _l	t _w	b _f	d _f	d _w	t _f	F _y	F _u	k ₁	k ₂	
WT6x6	27.2	21.6	21 1/2	0.595	Yes	6.42	0%	0.830	1/4	37	37	0	0
WT8x8	24.6	21.4	21 1/2	0.585	Yes	6.36	0%	0.830	1/4	37	37	0	0
WT10x10	21.2	21.2	21 1/2	0.585	Yes	6.30	0%	0.744	1/4	37	37	0	0
WT12x12	20.3	21.1	21 1/2	0.585	Yes	6.27	0%	0.682	1/4	37	37	0	0
WT14x14	18.2	21.0	21 1/2	0.585	Yes	6.20	0%	0.615	1/4	37	37	0	0
WT16x16	16.2	20.8	20 3/4	0.585	Yes	6.14	0%	0.552	1/4	37	37	0	0
WT18x18	14.1	20.8	20 3/4	0.585	Yes	6.08	0%	0.485	1/4	37	37	0	0
WT20x20	12.0	20.7	20 3/4	0.585	Yes	6.02	0%	0.420	1/4	37	37	0	0
WT22x22	10.0	20.6	20 3/4	0.585	Yes	5.96	0%	0.354	1/4	37	37	0	0
WT24x24	8.0	20.5	20 3/4	0.585	Yes	5.90	0%	0.288	1/4	37	37	0	0
WT26x26	6.0	20.4	20 3/4	0.585	Yes	5.84	0%	0.222	1/4	37	37	0	0
WT28x28	4.0	20.3	20 3/4	0.585	Yes	5.78	0%	0.156	1/4	37	37	0	0
WT30x30	2.0	20.2	20 3/4	0.585	Yes	5.72	0%	0.090	1/4	37	37	0	0
WT36x36	1.0	20.1	20 3/4	0.585	Yes	5.66	0%	0.024	1/4	37	37	0	0

**Table 1-1 (continued)
W-Shapes
Properties**

Shape WFL	Section Modulus in. ³		Axis X-X						Axis Y-Y						Torsional Properties		
	S _x	S _y	I _x	I _y	J	C _x	C _y	F _x	F _y	F _x	F _y	F _x	F _y	F _x	F _y	J	C _w
WT6	10.9	10.9	167	167	0.33	3.00	3.00	3.00	3.00	3.00	3.00	3.00	3.00	3.00	3.00	0.75	4.40
WT8	18.8	18.8	305	305	0.57	3.75	3.75	3.75	3.75	3.75	3.75	3.75	3.75	3.75	3.75	1.10	6.50
WT10	27.9	27.9	470	470	0.81	4.50	4.50	4.50	4.50	4.50	4.50	4.50	4.50	4.50	4.50	1.45	8.60
WT12	38.0	38.0	660	660	1.05	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	1.80	10.70
WT14	49.0	49.0	880	880	1.30	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	2.15	12.80
WT16	60.8	60.8	1130	1130	1.54	6.75	6.75	6.75	6.75	6.75	6.75	6.75	6.75	6.75	6.75	2.50	14.90
WT18	73.3	73.3	1400	1400	1.79	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50	2.85	17.00
WT20	86.4	86.4	1700	1700	2.03	8.25	8.25	8.25	8.25	8.25	8.25	8.25	8.25	8.25	8.25	3.20	19.10
WT22	100.0	100.0	2020	2020	2.28	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	3.55	21.20
WT24	114.0	114.0	2360	2360	2.52	9.75	9.75	9.75	9.75	9.75	9.75	9.75	9.75	9.75	9.75	3.90	23.30
WT26	128.0	128.0	2720	2720	2.77	10.50	10.50	10.50	10.50	10.50	10.50	10.50	10.50	10.50	10.50	4.25	25.40
WT28	142.0	142.0	3100	3100	3.01	11.25	11.25	11.25	11.25	11.25	11.25	11.25	11.25	11.25	11.25	4.60	27.50
WT30	156.0	156.0	3500	3500	3.26	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	4.95	29.60
WT36	199.0	199.0	4420	4420	3.74	13.50	13.50	13.50	13.50	13.50	13.50	13.50	13.50	13.50	13.50	5.65	34.80
WT40	230.0	230.0	4960	4960	4.00	14.25	14.25	14.25	14.25	14.25	14.25	14.25	14.25	14.25	14.25	5.95	36.90
WT44	259.0	259.0	5520	5520	4.25	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	6.25	39.00
WT48	287.0	287.0	6100	6100	4.50	15.75	15.75	15.75	15.75	15.75	15.75	15.75	15.75	15.75	15.75	6.55	41.10
WT52	314.0	314.0	6700	6700	4.75	16.50	16.50	16.50	16.50	16.50	16.50	16.50	16.50	16.50	16.50	6.85	43.20
WT56	340.0	340.0	7320	7320	5.00	17.25	17.25	17.25	17.25	17.25	17.25	17.25	17.25	17.25	17.25	7.15	45.30
WT60	365.0	365.0	7960	7960	5.25	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	7.45	47.40
WT66	415.0	415.0	9120	9120	5.75	19.50	19.50	19.50	19.50	19.50	19.50	19.50	19.50	19.50	19.50	8.05	53.60
WT72	464.0	464.0	10300	10300	6.25	21.00	21.00	21.00	21.00	21.00	21.00	21.00	21.00	21.00	21.00	8.65	59.80
WT78	512.0	512.0	11500	11500	6.75	22.50	22.50	22.50	22.50	22.50	22.50	22.50	22.50	22.50	22.50	9.25	66.00
WT84	560.0	560.0	12700	12700	7.25	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	9.85	72.20
WT90	608.0	608.0	13900	13900	7.75	25.50	25.50	25.50	25.50	25.50	25.50	25.50	25.50	25.50	25.50	10.45	78.40
WT96	656.0	656.0	15100	15100	8.25	27.00	27.00	27.00	27.00	27.00	27.00	27.00	27.00	27.00	27.00	11.05	84.60
WT102	704.0	704.0	16300	16300	8.75	28.50	28.50	28.50	28.50	28.50	28.50	28.50	28.50	28.50	28.50	11.65	90.80
WT108	752.0	752.0	17500	17500	9.25	30.00	30.00	30.00	30.00	30.00	30.00	30.00	30.00	30.00	30.00	12.25	97.00
WT114	800.0	800.0	18700	18700	9.75	31.50	31.50	31.50	31.50	31.50	31.50	31.50	31.50	31.50	31.50	12.85	103.20
WT120	848.0	848.0	19900	19900	10.25	33.00	33.00	33.00	33.00	33.00	33.00	33.00	33.00	33.00	33.00	13.45	109.40
WT126	896.0	896.0	21100	21100	10.75	34.50	34.50	34.50	34.50	34.50	34.50	34.50	34.50	34.50	34.50	14.05	115.60
WT132	944.0	944.0	22300	22300	11.25	36.00	36.00	36.00	36.00	36.00	36.00	36.00	36.00	36.00	36.00	14.65	121.80
WT138	992.0	992.0	23500	23500	11.75	37.50	37.50	37.50	37.50	37.50	37.50	37.50	37.50	37.50	37.50	15.25	128.00
WT144	1040.0	1040.0	24700	24700	12.25	39.00	39.00	39.00	39.00	39.00	39.00	39.00	39.00	39.00	39.00	15.85	134.20
WT150	1088.0	1088.0	25900	25900	12.75	40.50	40.50	40.50	40.50	40.50	40.50	40.50	40.50	40.50	40.50	16.45	140.40
WT156	1136.0	1136.0	27100	27100	13.25	42.00	42.00	42.00	42.00	42.00	42.00	42.00	42.00	42.00	42.00	17.05	146.60
WT162	1184.0	1184.0	28300	28300	13.75	43.50	43.50	43.50	43.50	43.50	43.50	43.50	43.50	43.50	43.50	17.65	152.80
WT168	1232.0	1232.0	29500	29500	14.25	45.00	45.00	45.00	45.00	45.00	45.00	45.00	45.00	45.00	45.00	18.25	159.00
WT174	1280.0	1280.0	30700	30700	14.75	46.50	46.50	46.50	46.50	46.50	46.50	46.50	46.50	46.50	46.50	18.85	165.20
WT180	1328.0	1328.0	31900	31900	15.25	48.00	48.00	48.00	48.00	48.00	48.00	48.00	48.00	48.00	48.00	19.45	171.40
WT186	1376.0	1376.0	33100	33100	15.75	49.50	49.50	49.50	49.50	49.50	49.50	49.50	49.50	49.50	49.50	20.05	177.60
WT192	1424.0	1424.0	34300	34300	16.25	51.00	51.00	51.00	51.00	51.00	51.00	51.00	51.00	51.00	51.00	20.65	183.80
WT198	1472.0	1472.0	35500	35500	16.75	52.50	52.50	52.50	52.50	52.50	52.50	52.50	52.50	52.50	52.50	21.25	190.00
WT204	1520.0	1520.0	36700	36700	17.25	54.00	54.00	54.00	54.00	54.00	54.00	54.00	54.00	54.00	54.00	21.85	196.20
WT210	1568.0	1568.0	37900	37900	17.75	55.50	55.50	55.50	55.50	55.50	55.50	55.50	55.50	55.50	55.50	22.45	202.40
WT216	1616.0	1616.0	39100	39100	18.25	57.00	57.00	57.00	57.00	57.00	57.00	57.00	57.00	57.00	57.00	23.05	208.60
WT222	1664.0	1664.0	40300	40300	18.75	58.50	58.50	58.50	58.50	58.50	58.50	58.50	58.50	58.50	58.50	23.65	214.80
WT228	1712.0	1712.0	41500	41500	19.25	60.00	60.00	60.00	60.00	60.00	60.00	60.00	60.00	60.00	60.00	24.25	221.00
WT234	1760.0	1760.0	42700	42700	19.75	61.50	61.50	61.50	61.50	61.50	61.50	61.50	61.50	61.50	61.50	24.85	227.20
WT240	1808.0	1808.0	43900	43900	20.25	63.00	63.00	63.00	63.00	63.00	63.00	63.00	63.00	63.00	63.00	25.45	233.40
WT246	1856.0	1856.0	45100	45100	20.75	64.50	64.50	64.50	64.50	64.50	64.50	64.50	64.50	64.50	64.50	26.05	239.60
WT252	1904.0	1904.0	46300	46300	21.25	66.00	66.00	66.00	66.00	66.00	66.00	66.00	66.00	66.00	66.00	26.65	245.80
WT258	1952.0	1952.0	47500</														

Table 1-1 (continued)
W-Shapes
 Dimensions

Shape	Area, A_g		Depth, d	Web Thickness, t_w	Web C_x	Flange Thickness, t_f		Stabilities		r_x	r_y	Weld- ment Factor					
	A_g	A_n				b_f	t_f	A_{st}	A_{st}				r_x	r_y			
W16x30	29.4	37.0	17	0.345	Na	Na	10.4	17%	0.685	1	1.39	1%	17%	3%	11%	13%	3%
W16x27	26.2	34.8	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	1.30	1%	17%	3%	11%	13%	3%
W16x25	24.7	33.1	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	1.26	1%	17%	3%	11%	13%	3%
W16x22	22.8	31.4	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	1.22	1%	17%	3%	11%	13%	3%
W16x20	21.3	29.9	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	1.18	1%	17%	3%	11%	13%	3%
W16x18	20.0	28.6	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	1.14	1%	17%	3%	11%	13%	3%
W16x17	19.3	28.0	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	1.12	1%	17%	3%	11%	13%	3%
W16x15	17.9	26.6	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	1.08	1%	17%	3%	11%	13%	3%
W16x14	17.3	26.0	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	1.06	1%	17%	3%	11%	13%	3%
W16x13	16.7	25.4	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	1.04	1%	17%	3%	11%	13%	3%
W16x12	16.2	24.9	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	1.02	1%	17%	3%	11%	13%	3%
W16x11	15.7	24.4	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	1.00	1%	17%	3%	11%	13%	3%
W16x10	15.2	23.9	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	0.98	1%	17%	3%	11%	13%	3%
W16x9	14.7	23.4	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	0.96	1%	17%	3%	11%	13%	3%
W16x8	14.2	22.9	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	0.94	1%	17%	3%	11%	13%	3%
W16x7	13.7	22.4	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	0.92	1%	17%	3%	11%	13%	3%
W16x6	13.2	21.9	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	0.90	1%	17%	3%	11%	13%	3%
W16x5	12.7	21.4	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	0.88	1%	17%	3%	11%	13%	3%
W16x4	12.2	20.9	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	0.86	1%	17%	3%	11%	13%	3%
W16x3	11.7	20.4	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	0.84	1%	17%	3%	11%	13%	3%
W16x2	11.2	19.9	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	0.82	1%	17%	3%	11%	13%	3%
W16x1	10.7	19.4	16 1/2	0.325	Na	Na	10.4	17%	0.670	1	0.80	1%	17%	3%	11%	13%	3%

* Shapes in shaded for comparison with $r_x = 30$ in.
 † The actual area, combination and dimension of flange components should be compared with the geometry of the cross section.
 ‡ Flange thickness t_f is the thickness of the flange.
 § These notes do not include the A_g and A_n used to obtain r_x and r_y .
 ¶ r_x and r_y are the radii of gyration about the x and y axes, respectively.

Table 1-1 (continued)
W-Shapes
 Properties

Shape	Moment of Inertia, I		Depth, d	Web		Flange		Section Modulus, S_x		Plastic Section Modulus, Z_x		Torsion		r_x	r_y	J	C_w
	I_x	I_y		t_w	t_f	A_{st}	A_{st}	S_x	S_y	Z_x	Z_y	J	C_w				
W16x30	294	370	17	0.345	1.39	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x27	262	348	16 1/2	0.325	1.30	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x25	247	331	16 1/2	0.325	1.26	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x22	228	314	16 1/2	0.325	1.22	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x20	213	299	16 1/2	0.325	1.18	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x18	200	286	16 1/2	0.325	1.14	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x17	193	280	16 1/2	0.325	1.12	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x15	179	266	16 1/2	0.325	1.08	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x14	173	260	16 1/2	0.325	1.06	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x13	167	254	16 1/2	0.325	1.04	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x12	162	249	16 1/2	0.325	1.02	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x11	157	244	16 1/2	0.325	1.00	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x10	152	239	16 1/2	0.325	0.98	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x9	147	234	16 1/2	0.325	0.96	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x8	142	229	16 1/2	0.325	0.94	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x7	137	224	16 1/2	0.325	0.92	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x6	132	219	16 1/2	0.325	0.90	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x5	127	214	16 1/2	0.325	0.88	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x4	122	209	16 1/2	0.325	0.86	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x3	117	204	16 1/2	0.325	0.84	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x2	112	199	16 1/2	0.325	0.82	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%
W16x1	107	194	16 1/2	0.325	0.80	1%	17%	3%	11%	13%	3%	11%	13%	3%	11%	13%	3%



W16-W14



Table 1-1 (continued)
W-Shapes
Dimensions

Shape	Area, A		Depth, d	Web		Flange		Thickness		Distances		Y	Z	W _{pl} -axis radius of gyration	
	A_g	A_w		t_w	t_f	t_f	t_f	t_f	t_f	k	k_x				k_y
W14x132	36.8	14.7	14.96	0.645	14.7	14.7	1.63	2.79	17% 1.63	1.63	27% 1.63	17% 1.63	10	0%	
W14x110	30.5	14.5	14.96	0.580	14.5	14.5	1.54	2.76	11% 1.54	1.54	27% 1.54	11%	10	0%	
W14x90	24.2	14.2	14.96	0.525	14.2	14.2	1.46	2.76	11%	1.46	27% 1.46	11%	10	0%	
W14x74	20.0	14.0	14.96	0.465	14.0	14.0	1.38	2.76	11%	1.38	27% 1.38	11%	10	0%	
W14x54	15.7	13.7	14.96	0.405	13.7	13.7	1.31	2.76	11%	1.31	2.76	11%	10	0%	
W14x38	11.2	11.2	14.96	0.310	11.2	11.2	1.16	2.76	11%	1.16	2.76	11%	10	0%	
W14x30	9.0	9.0	14.96	0.255	9.0	9.0	1.10	2.76	11%	1.10	2.76	11%	10	0%	
W14x24	7.2	7.2	14.96	0.210	7.2	7.2	1.03	2.76	11%	1.03	2.76	11%	10	0%	
W14x18	5.8	5.8	14.96	0.170	5.8	5.8	0.96	2.76	11%	0.96	2.76	11%	10	0%	
W14x16	5.2	5.2	14.96	0.160	5.2	5.2	0.93	2.76	11%	0.93	2.76	11%	10	0%	
W14x12	4.0	4.0	14.96	0.125	4.0	4.0	0.88	2.76	11%	0.88	2.76	11%	10	0%	
W14x10	3.5	3.5	14.96	0.115	3.5	3.5	0.85	2.76	11%	0.85	2.76	11%	10	0%	
W14x8	2.9	2.9	14.96	0.090	2.9	2.9	0.81	2.76	11%	0.81	2.76	11%	10	0%	
W14x6	2.3	2.3	14.96	0.075	2.3	2.3	0.78	2.76	11%	0.78	2.76	11%	10	0%	
W14x4	1.8	1.8	14.96	0.060	1.8	1.8	0.75	2.76	11%	0.75	2.76	11%	10	0%	
W12x30	11.2	14.2	14.49	0.480	12.0	12.0	1.33	2.76	11%	1.33	2.76	11%	10	0%	
W12x24	9.0	11.0	14.49	0.405	10.0	10.0	1.25	2.76	11%	1.25	2.76	11%	10	0%	
W12x18	7.2	9.2	14.49	0.330	8.0	8.0	1.17	2.76	11%	1.17	2.76	11%	10	0%	
W12x16	6.3	8.3	14.49	0.300	7.0	7.0	1.14	2.76	11%	1.14	2.76	11%	10	0%	
W12x14	5.4	7.4	14.49	0.270	6.0	6.0	1.11	2.76	11%	1.11	2.76	11%	10	0%	
W12x12	4.7	6.7	14.49	0.240	5.0	5.0	1.08	2.76	11%	1.08	2.76	11%	10	0%	
W12x10	4.0	6.0	14.49	0.210	4.0	4.0	1.05	2.76	11%	1.05	2.76	11%	10	0%	
W12x8	3.3	5.3	14.49	0.180	3.0	3.0	1.02	2.76	11%	1.02	2.76	11%	10	0%	
W12x6	2.7	4.7	14.49	0.150	2.5	2.5	0.99	2.76	11%	0.99	2.76	11%	10	0%	
W12x4	2.1	4.1	14.49	0.120	2.0	2.0	0.96	2.76	11%	0.96	2.76	11%	10	0%	
W10x54	15.8	13.8	13.71	0.510	14.0	14.0	1.28	2.76	11%	1.28	2.76	11%	10	0%	
W10x48	14.2	12.2	13.71	0.465	13.0	13.0	1.25	2.76	11%	1.25	2.76	11%	10	0%	
W10x42	12.7	10.7	13.71	0.420	12.0	12.0	1.22	2.76	11%	1.22	2.76	11%	10	0%	
W10x36	11.1	9.1	13.71	0.375	11.0	11.0	1.19	2.76	11%	1.19	2.76	11%	10	0%	
W10x30	9.5	7.5	13.71	0.330	9.0	9.0	1.16	2.76	11%	1.16	2.76	11%	10	0%	
W10x24	8.0	6.0	13.71	0.285	7.5	7.5	1.13	2.76	11%	1.13	2.76	11%	10	0%	
W10x18	6.4	4.4	13.71	0.240	6.0	6.0	1.10	2.76	11%	1.10	2.76	11%	10	0%	
W10x16	5.7	3.7	13.71	0.230	5.0	5.0	1.09	2.76	11%	1.09	2.76	11%	10	0%	
W10x14	5.0	3.0	13.71	0.220	4.0	4.0	1.08	2.76	11%	1.08	2.76	11%	10	0%	
W10x12	4.4	2.4	13.71	0.210	3.0	3.0	1.07	2.76	11%	1.07	2.76	11%	10	0%	
W10x10	3.8	1.8	13.71	0.200	2.5	2.5	1.06	2.76	11%	1.06	2.76	11%	10	0%	
W10x8	3.2	1.2	13.71	0.190	2.0	2.0	1.05	2.76	11%	1.05	2.76	11%	10	0%	
W10x6	2.6	0.6	13.71	0.180	1.5	1.5	1.04	2.76	11%	1.04	2.76	11%	10	0%	
W10x4	2.0	0.0	13.71	0.170	1.0	1.0	1.03	2.76	11%	1.03	2.76	11%	10	0%	
W10x3	1.8	0.0	13.71	0.165	1.0	1.0	1.02	2.76	11%	1.02	2.76	11%	10	0%	
W8x31	9.1	13.1	13.24	0.510	10.0	10.0	1.28	2.76	11%	1.28	2.76	11%	10	0%	
W8x27	8.0	12.0	13.24	0.465	9.0	9.0	1.25	2.76	11%	1.25	2.76	11%	10	0%	
W8x24	7.2	11.0	13.24	0.420	8.0	8.0	1.22	2.76	11%	1.22	2.76	11%	10	0%	
W8x21	6.4	10.0	13.24	0.375	7.0	7.0	1.19	2.76	11%	1.19	2.76	11%	10	0%	
W8x18	5.6	9.0	13.24	0.330	6.0	6.0	1.16	2.76	11%	1.16	2.76	11%	10	0%	
W8x16	4.9	8.0	13.24	0.300	5.0	5.0	1.14	2.76	11%	1.14	2.76	11%	10	0%	
W8x14	4.3	7.0	13.24	0.270	4.0	4.0	1.11	2.76	11%	1.11	2.76	11%	10	0%	
W8x12	3.7	6.0	13.24	0.240	3.0	3.0	1.08	2.76	11%	1.08	2.76	11%	10	0%	
W8x10	3.1	5.0	13.24	0.210	2.5	2.5	1.05	2.76	11%	1.05	2.76	11%	10	0%	
W8x8	2.5	4.0	13.24	0.180	2.0	2.0	1.02	2.76	11%	1.02	2.76	11%	10	0%	
W8x6	2.0	3.0	13.24	0.150	1.5	1.5	0.99	2.76	11%	0.99	2.76	11%	10	0%	
W8x4	1.5	2.0	13.24	0.120	1.0	1.0	0.96	2.76	11%	0.96	2.76	11%	10	0%	
W6x30	8.8	12.8	12.75	0.510	9.0	9.0	1.28	2.76	11%	1.28	2.76	11%	10	0%	
W6x27	7.9	11.9	12.75	0.465	8.0	8.0	1.25	2.76	11%	1.25	2.76	11%	10	0%	
W6x24	7.1	11.0	12.75	0.420	7.0	7.0	1.22	2.76	11%	1.22	2.76	11%	10	0%	
W6x21	6.3	10.0	12.75	0.375	6.0	6.0	1.19	2.76	11%	1.19	2.76	11%	10	0%	
W6x18	5.5	9.0	12.75	0.330	5.0	5.0	1.16	2.76	11%	1.16	2.76	11%	10	0%	
W6x16	4.9	8.0	12.75	0.300	4.0	4.0	1.14	2.76	11%	1.14	2.76	11%	10	0%	
W6x14	4.3	7.0	12.75	0.270	3.0	3.0	1.11	2.76	11%	1.11	2.76	11%	10	0%	
W6x12	3.7	6.0	12.75	0.240	2.5	2.5	1.08	2.76	11%	1.08	2.76	11%	10	0%	
W6x10	3.1	5.0	12.75	0.210	2.0	2.0	1.05	2.76	11%	1.05	2.76	11%	10	0%	
W6x8	2.5	4.0	12.75	0.180	1.5	1.5	1.02	2.76	11%	1.02	2.76	11%	10	0%	
W6x6	2.0	3.0	12.75	0.150	1.0	1.0	0.99	2.76	11%	0.99	2.76	11%	10	0%	
W6x4	1.5	2.0	12.75	0.120	1.0	1.0	0.96	2.76	11%	0.96	2.76	11%	10	0%	
W6x3	1.3	1.5	12.75	0.115	1.0	1.0	0.95	2.76	11%	0.95	2.76	11%	10	0%	
W4x26	7.8	11.8	12.29	0.510	8.0	8.0	1.28	2.76	11%	1.28	2.76	11%	10	0%	
W4x22	6.9	10.9	12.29	0.465	7.0	7.0	1.25	2.76	11%	1.25	2.76	11%	10	0%	
W4x18	5.9	9.9	12.29	0.420	6.0	6.0	1.22	2.76	11%	1.22	2.76	11%	10	0%	
W4x16	5.3	9.0	12.29	0.375	5.0	5.0	1.19	2.76	11%	1.19	2.76	11%	10	0%	
W4x14	4.7	8.0	12.29	0.330	4.0	4.0	1.16	2.76	11%	1.16	2.76	11%	10	0%	
W4x12	4.1	7.0	12.29	0.285	3.0	3.0	1.13	2.76	11%	1.13	2.76	11%	10	0%	
W4x10	3.5	6.0	12.29	0.240	2.5	2.5	1.10	2.76	11%	1.10	2.76	11%	10	0%	
W4x8	2.9	5.0	12.29	0.200	2.0	2.0	1.07	2.76	11%	1.07	2.76	11%	10	0%	
W4x6	2.3	4.0	12.29	0.160	1.5	1.5	1.04	2.76	11%	1.04	2.76	11%	10	0%	
W4x4	1.7	3.0	12.29	0.120	1.0	1.0	1.01	2.76	11%	1.01	2.76	11%	10	0%	
W36x100	33.7	17.7	35.96	0.850	35.0	35.0	1.81	2.76	11%	1.81	2.76	11%	10	0%	
W36x84	29.7	16.2	3												

$F_y = 50$ ksi

Table 3-2 (continued)

W Shapes

Selection by Z_x

Z_x

Shape	Z_x in. ³	M_{px}/Ω_b		$\phi_p M_{px}$		M_{cy}/Ω_c		$\phi_y M_{cy}$		BF		L_p ft	L_r ft	L_b in. ⁴	K_{cx}/Ω_c		$\phi_y K_{cx}$	
		kip-ft		kip-ft		kip-ft		kips		kips					kips		kips	
		ASD	LRFD	ASD	LRFD	ASD	LRFD	ASD	LRFD	ASD	LRFD				ASD	LRFD		
W30x116	378	943	1420	575	864	24.7	37.2	7.74	32.6	4930	339	509						
W21x147	373	931	1400	575	864	13.8	20.7	10.4	36.3	3630	318	476						
W24x131	370	923	1390	575	864	16.3	24.5	10.5	31.9	4020	296	444						
W18x158	356	888	1340	541	814	10.5	15.7	9.68	42.8	3060	319	479						
W14x193	355	886	1330	541	814	5.27	7.92	14.3	79.7	2400	276	413						
W12x210	348	868	1310	510	767	4.24	6.38	11.6	96.0	2140	347	521						
W30x108	346	863	1300	522	785	23.7	36.6	7.59	22.0	4470	325	488						
W27x114	343	856	1290	522	785	21.7	32.6	7.70	23.1	4080	311	467						
W21x132	333	831	1250	515	774	13.3	20.0	10.3	34.1	3220	284	426						
W24x117	327	816	1230	508	764	15.3	23.1	10.4	30.4	3540	267	400						
W18x143	322	803	1210	493	740	10.4	15.6	9.61	39.6	2750	285	427						
W14x176	320	798	1200	491	738	5.22	7.84	14.2	73.2	2140	253	379						
W30x99	312	778	1170	470	706	22.2	33.3	7.42	21.4	3990	308	463						
W12x190	311	776	1170	459	690	4.18	6.20	11.5	87.3	1890	305	457						
W21x122	307	766	1150	477	717	12.9	19.4	10.3	32.7	2960	280	390						
W27x102	305	761	1140	466	701	20.2	30.3	7.59	22.2	3620	279	419						
W18x130	290	724	1090	447	672	10.2	15.3	9.54	36.7	2460	258	387						
W24x104	289	721	1080	451	677	14.3	21.5	10.3	29.2	3100	241	361						
W14x159	287	716	1080	444	667	5.16	7.79	14.1	68.7	1900	223	335						
W30x90*	283	706	1060	428	643	20.5	30.9	7.38	20.9	3610	249	375						
W24x103	280	699	1050	428	643	18.2	27.4	7.03	21.9	3000	270	405						
W21x111	279	696	1050	435	654	12.4	18.7	10.2	31.3	2670	237	355						
W27x94	278	694	1040	424	638	19.1	28.8	7.49	21.6	3270	264	396						
W12x170	275	686	1030	410	617	4.11	6.18	11.4	78.5	1650	269	404						
W18x119	262	654	983	403	606	10.1	15.2	9.50	34.3	2190	249	373						
W14x145	260	649	975	405	609	5.71	7.68	14.1	61.7	1710	201	302						
W24x94	254	634	953	388	583	17.3	26.0	6.99	21.2	2700	250	376						
W21x101	253	631	949	396	596	11.6	17.7	10.2	30.1	2420	214	320						
W27x84	244	609	915	372	559	17.6	26.4	7.31	20.8	2850	246	369						
W12x152	243	606	911	365	549	4.07	6.11	11.3	70.6	1430	239	358						
W16x132	234	584	878	365	549	5.13	7.70	13.3	56.0	1530	189	284						
W18x106	230	574	863	358	536	9.70	14.6	9.40	31.8	1910	221	332						

* Shape does not meet the M_{px} limit for shear in Specification Section G2.1a with $F_y = 50$ ksi, $\Omega_b = 1.67$, $\phi_v = 0.90$.

ASD	LRFD
$\Omega_b = 1.67$ $\Omega_c = 1.50$	$\phi_v = 0.90$ $\phi_y = 1.00$



Table 3-2 (continued)
W Shapes
 Selection by Z_x

 $F_y = 50 \text{ ksi}$

Shape	Z_x in. ³	M_{pr}/Ω_b		M_{pr}/Ω_b		BF		L_p ft	L_r ft	L_x in. ⁴	V_{pr}/Ω_v	
		kip-ft	kip-ft	kip-ft	kip-ft	kip	kip				kip	kip
		ASD	LRFD	ASD	LRFD	ASD	LRFD				ASD	LRFD
W24x84	224	599	840	342	515	16.2	24.3	6.89	20.3	2370	227	340
W21x83	221	551	829	335	504	14.6	21.9	6.50	21.3	2070	251	376
W12x136	214	534	803	325	488	4.01	6.03	11.2	63.3	1240	212	318
W14x120	212	529	795	332	499	5.09	7.64	13.2	52.0	1380	171	256
W18x97	211	528	791	328	494	9.45	14.2	9.36	30.3	1750	199	298
W24x76	200	499	750	307	462	15.0	22.5	6.70	19.6	2100	210	316
W16x100	198	494	743	306	459	7.90	11.9	8.87	32.7	1490	199	298
W21x83	196	489	735	299	448	13.8	20.8	6.46	20.2	1830	221	331
W14x109	192	479	720	302	454	5.02	7.54	13.2	48.4	1240	150	226
W18x86	186	464	698	290	436	9.04	13.6	9.29	28.5	1070	177	265
W12x120	186	464	698	285	428	3.95	5.93	11.1	56.5	1530	186	279
W24x68	177	442	664	289	404	14.1	21.2	6.61	18.8	1830	197	296
W16x89	175	437	656	271	407	7.74	11.6	8.80	30.2	1300	176	264
W14x99 ^f	173	430	646	274	412	4.89	7.35	13.5	45.3	1110	137	206
W21x73	172	429	645	264	396	12.9	19.4	6.39	19.2	1600	193	290
W12x106	164	409	615	253	381	3.93	5.90	11.0	50.7	933	157	236
W18x76	163	407	611	255	383	8.49	12.8	9.22	27.1	1330	155	232
W21x68	160	399	600	245	368	12.5	18.8	6.36	18.7	1480	182	273
W14x90 ^f	157	382	573	250	375	4.80	7.22	15.2	42.6	999	123	185
W24x62	153	382	574	229	344	16.0	24.1	4.87	14.4	1550	204	306
W16x77	150	374	563	234	352	7.34	11.0	8.72	27.8	1110	150	225
W12x96	147	367	551	229	344	3.67	5.61	10.9	46.6	833	140	210
W10x112	147	367	551	220	331	2.68	4.02	9.47	64.3	716	172	257
W18x71	146	364	548	222	333	10.5	15.7	6.00	19.6	1170	183	274
W21x62	144	366	540	222	333	11.6	17.4	6.25	18.1	1330	188	282
W14x82	139	347	521	215	323	5.43	8.16	8.76	33.1	881	146	219
W24x56 ^f	134	334	503	199	289	14.8	22.2	4.73	13.9	1350	187	281
W18x65	133	332	499	204	307	9.92	14.9	5.97	18.8	1070	165	248
W12x87	132	329	495	206	310	3.04	5.76	10.8	43.0	740	129	194
W16x67	130	324	488	204	307	6.91	10.4	8.69	26.1	954	129	194
W10x100	130	324	488	196	294	2.66	4.01	9.36	57.7	623	151	226
W21x57	129	322	484	194	291	13.4	20.1	4.77	14.3	1170	171	256

ASD

LRFD

¹ Shape exceeds compact limit for flexure with $F_y = 50 \text{ ksi}$.² Shape does not meet the H/V_u limit for shear in Specification Section G2.1a with $F_y = 50 \text{ ksi}$. $C_b = 1.07$, $\phi_b = 0.90$.
 $C_b = 1.87$
 $C_b = 1.50$
 $\phi_b = 0.90$
 $\phi_b = 1.00$