(10)

Date: 23 December, 2023 (Moming)

Name of the Program: B.Sc. in EEE Semester: 5th

ISLAMIC UNIVERSITY OF TECHNOLOGY (IUT) ORGANISATION OF ISLAMIC COOPERATION (OIC) DEPARTMENT OF ELECTRICAL AND ELECTRONIC ENGINEERING

Semester Final Examination Course No.: EEE 4541 Course Title: Wireless Communication Winter Semester, A. Y. 2022-2023 Time: 3 Hours Full Marks: 150

There are 6 (six) questions. Answer all 6 (six) questions. The symbols have their usual meanings. Programmable calculators are not allowed. Marks of each question and corresponding COs and POs are written in the brackets.

7 (CO1, PO1)	Explain how space diversity can improve signal reception. Explain the reason for the use of smaller cell size with time.	a)	1.
(CO1, PO1)	State how many primary scrambling codes (PSCs) are available. Discuss the justification of this number.	b)	
12 (CO2, PO2)	The height of a transmitter is 20 m and it is transmitting with EIRP 50 dBm. The transmitter and the receiver are 10 km away from each other. The frequency of the signal is 1.5 GHz. The path difference between the direct wave and the wave reflected from the ground is 1.6 cm. The received power is -6.2 dBm. Calculate the gain of the receiving antenna. Consider 10 web Reglocation	c)	
(CO1, PO1)	Discuss the reason for the higher popularity of empirical path loss models. State the advantages of International Terrestrial Cable (ITC) compared to submarine cables. State when a connection with SEA-ME-WE-6 is expected in Bangladesh.	a)	2.
5 (CO1,	If the cell size is increased changing the downtilt instead of changing the transmit power, determine the possible advantage.	b)	
PO1) 12 (CO2, PO2)	The EIRP of the base station is 45 dBm. The MS antenna gain is 0 dB, A1 500 m from the base station, the received power is found -50 dBm. The minimum tolerable power is considered -100 dBm. The path loss exponent is 3.5. Determine the outage probability at a distance 8 km. Use log-normal shadowing with standard deviation 4.5.	c)	
6 (CO1,	State how much packet errors may be allowed during MCS selection in 4G. Discuss the justification for this percentage.	a)	3.
PO1) 6 (CO1, PO1)	For each of the following applications, find which layers will perform retransmissions in the case of errors: Voice, live streaming video, buffered streaming video, real time gaming.	b)	
7	Determine if the following two codes are orthogonal or not.	c)	
(CO2, PO2)	1 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1		
6	Find the frequency of local oscillator when someone tunes to 98 MHz for FM radio.	d)	

(CO2,

	a)	Discuss the purpose of TTL (time to live) field in IP header. For VoIP packets with IPv6, find the ratio of size of TCP/IP header and payload size.									
	b)	Explain slow start procedure. State what happens when TCP reaches slow start threshold (sithresh).									
	c)	For each of the following parameters, find which one between the base station and t UE (phone) decides the value.									
		 Transmit power in domiliak Transmit power in uplink Modulation level in downlink Modulation level in uplink Code rate in downlink Code rate in uplink 	PO1)								
	d)	Discuss the disadvantages of Infrared (IR) communication. Discuss how multiple users can share the unlicensed radio bands.									
	a)	Discuss the possible problems with ordinary TCP when there is a wireless link. Explain the operation of Mobile TCP (M-TCP).	PO1) 8 (CO1, PO1)								
	b)	Assume that all bytes are sequentially numbered in TCP buffers. The buffer on the receiving side can accommodate 4096 bytes. The effective window size for the sender is 800 bytes. The congestion window size is 1800 bytes. The TCP sequence numbers are given below for the following parameters.									
		LastByteRcvd = 65889 LastByteRead = 63635 LastByteSent = 66000									
		Determine the sequence number of LastByteAcked parameter.									
	c)	Discuss why sky wave provides better communication at night. Compare GEO satellites and LEO satellites in terms of advantages and disadvantages. Explain the function of thrusters.	9 (CO1, PO1)								
i,	a)	For packet routing, compare the time required in Triangular Routing and the time required in Reverse Tunneling.									
	b)	Distinguish between WPAN and LPWAN, and give their examples. Discuss the special requirements for wireless IoT.									
	c)	Find out the problems that may occur if a Wireless Local Area Network (WLAN) operates in the following ways.									
		 Transmission of Request-to-Send (RTS) is used but the transmission of Clear- to-Send (CTS) is not used. Transmission of RTS is used but then CTS is transmitted with significant delay. Transmission of Acknowledgment (ACK) is not used. 	PO1)								
	d)	A 4G user is allocated 900 kHz in downlink. He is using 256-QAM and code rate ½. Determine the time required to download a 10 MB file.	8 (CO2, PO2)								

STANDARD NORMAL DISTRIBUTION: Table Values Represent AREA to the LEFT of the Z score.										
Z	.00	.01	.02	.03	.04	.05	.06	.07	.08	.09
-3.9	.00005	.00005	.00004	.00004	.00004	.00004	.00004	.00004	.00003	.00003
-3.8	.00007	.00007	.00007	.00006	.00006	.00006	.00005	.00005	.00005	.00005
-3.7	.00011	.00010	.00010	.00010	.00009	.00009	\$0000.	.00008	.00008	.00008
-3.6	.00016	.00015	.00015	.00014	.00014	.00013	.00013	.00012	.00012	.00011
-3.5	.00023	.00022	.00022	.00021	.00020	.00019	.00019	.00018	.00017	.00017
-3.4	.00034	.00032	.00031	.00030	.00029	.00028	.00027	.00026	.00025	.00024
-3.3	.00048	.00047	.00045	.00043	.00042	.00040	.00039	.00038	.00036	.00035
-3.2	.00069	.00066	.00064	.00062	.00060	.00058	.00056	.00054	.00052	.00050
-3.1	.00097	.00094	.00090	.00087	.00084	.00082	.00079	.00076	.00074	.00071
-3.0	.00135	.00131	.00126	.00122	.00118	.00114	.001111	.00107	.00104	.00100
-2.9	.00187	.00181	.00175	.00169	.00164	.00159	.00154	.00149	.00144	.00139
-2.8	.00256	.00248	.00240	.00233	.00226	.00219	.00212	.00205	.00199	.00193
-2.7	.00347	.00336	.00326	,00317	.00307	.00298	.00289	.00280	.00272	.00264
-2.6	.00466	.00453	.00440	.00427	.00415	.00402	.00391	.00379	.00368	.00357
-2.5	.00621	.00604	.00587	.00570	.00554	.00539	.00523	.00508	.00494	.00480
-2.4	.00820	.00798	.00776	.00755	.00734	.00714	.00695	.00676	.00657	.00639
-2.3	.01072	.01044	.01017	.00990	.00964	.00939	.00914	.00889	.00866	.00842
-2.2	.01390	.01355	.01321	.01287	.01255	.01222	.01191	.01160	.01130	.01101
-2.1	.01786	.01743	.01700	.01659	.01618	.01578	.01539	.01500	.01463	.01426
-2.0	.02275	.02222	.02169	.02118	.02068	.02018	.01970	.01923	.01876	.01831
-1.9	.02872	.02807	.02743	.02680	.02619	.02559	.02500	.02442	.02385	.02330
-1.8	.03593	.03515	.03438	.03362	.03288	.03216	.03144	.03074	.03005	.02938
-1.7	.04457	.04363	.04272	.04182	.04093	.04006	.03920	.03836	.03754	.03673
-1.6	.05480	.05370	.05262	.05155	.05050	.04947	.04846	.04746	.04648	.04551
-1.5	.06681	.06552	.06426	.06301	.06178	.06057	.05938	.05821	.05705	.05592
-1.4	.08076	.07927	.07780	.07636	.07493	.07353	.07215	.07078	.06944	.06811
-1.3	.09680	.09510	.09342	.09176	.09012	.08851	.08691	.08534	.08379	.08226
-1.2	.11507	.11314	.11123	.10935	.10749	.10565	.10383	.10204	.10027	.09853
-1.1	.13567	.13350	.13136	.12924	.12714	.12507	.12302	.12100	.11900	.11702
-1.0	.15866	.15625	.15386	.15151	.14917	.14686	.14457	.14231	.14007	.13786
-0.9	.18406	.18141	.17879	.17619	.17361	.17106	.16853	.16602	.16354	.16109
-0.8		.20897	.20611	.20327	.20045	.19766	.19489	.19215	.18943	.18673
-0.7		.23885	.23576	.23270	.22965	.22663	.22363	.22065	.21770	.21476
-0.6		.27093	.26763	.26435	.26109	.25785	.25463	.25143	.24825	.24510
-0.5		.30503	.30153	.29806	.29460	.29116	.28774	.28434	.28096	.27760
-0.4		.34090	.33724	.33360	.32997	.32636	.32276	.31918	.31561	.31207
-0.3		.37828	.37448	.37070	.36693	.36317	.35942	.35569	.35197	.34827
-0.2		.41683	.41294	.40905	.40517	.40129	.39743	.39358	.38974	.38591
-0.1		.45620	.45224	.44828	,44433	.44038	.43644	.43251	.42858	.42465
-0.0	.50000	.49601	.49202	.48803	,48405	.48006	.47608	.47210	.46812	.46414

STANDARD NORMAL DISTRIBUTION: Table Values Represent APE 4 to the LEFT

- 1		Z .00	.01	.02	.03	ne values	Represen	t AREA t		T of the Z	score.
	0.	.0 .5000				.04	.05	.06	.07	.05	.09
	0.										_53586
	0.	2 .5792	5 .58317			.59483					.57535
	0.	3 .6179			.62930	.59483					.61409
	0.	4 .6554;			66640	.67003					.65173
	0.	5 .69146			.70194	.70540	.67364				.68793
	0.	6 .72575			.73565	.70540	.70384				.72240
	0.1	7 .75804	.76115	.76424	.76730	.77035	.74215				.75490
	0.1	8 .78814		.79389	.79673	.79955	.77337	.77637	.77935	.78230	.78524
	0.5	.81594	.81859	.82121	.82381	.82639	.80234	.80511	.80785	.81057	.81327
	1.0	.84134	.84375	.84614	.84849	.85083	.82894	.83147	.83398	.83646	.\$3891
	1.1		.86650	.\$6864	.87076	.87286	.85314	.85543	.85769	.85993	.86214
	1.2	.88493	.88686	.88877	.89065	.89251		.87698	.87900	.\$\$100	.88298
	1.3	.90320	.90490	.90658	.90824	.90938	.89435	.89617	.89796	.89973	.90147
	1.4	.91924	92073	.92220	.92364	.92507	.91149	.91309	.91466	.91621	.91774
	1.5	.93319	.93448	.93574	.93699	.92307	.92647	.92785	.92922	.93056	.93189
	1.6		.94630	.94738	.94845	.94950	.93943	.94062	.94179	.94295	.94408
	1.7		.95637	.95728	.95818	.95907	.95994	.95154	.95254	.95352	.95449
	1.8	.96407	.96485	.96562	.96638	.96712	.95994	.96080	.96164	.96246	.96327
	1.9	.97128	.97193	.97257	.97320	.97381	.97441	.96856	.96926	.96995	.97062
	2.0	.97725	.97778	.97831	.97882	.97932	.97982	.97500	.97558	.97615	.97670
	2.1	.98214	98257	.98300	.98341	.98382	.93422	98030	.98077	.98124	.98169
	2.2	.98610	.98645	.98679	.98713	.98745	.98422	.98461	.98500	.98537	-98574
	2.3	.98928	.98956	.98983	.99010	.99036	.99061	.98809	.98840	.98870	-98899
_	2.4	.99180	.99202	.99224	.99245	.99266	.99286	.99086	.99111	.99134	.99158
	2.5	.99379	.99396	.99413	.99430	.99446	.99461	.99305	.99324	.99343	.99361
	2.6	.99534	.99547	.99560	.99573	.99585	.99598	.99477	.99492	.99506	.99520
	2.7	.99653	.99664	.99674	99683	.99693	.99398	.99609	.99621	-99632	.99643
	2.8	.99744	.99752	.99760	.99767	.99774	.99781	.99711	.99720	-99728	.99736
	2.9	.99813	.99819	.99825	.99831	.99836	.99841	.99846	.99795	.99801	.99807
	3.0	.99865	.99869	.99874	.99878	.99882	.99886	.99889	.99851	.99856	.99861
	3.1	.99903	.99906	.99910	.99913	-99916	.99918	.99889	.99893	.99896	.99900
	3.2	.99931	.99934	.99936	.99938	.99940	.99942	.99944	.99924	.99926	.99929
	3.3	.99952	.99953	.99955	.99957	.99958	.99960	.99961	.99946	.99948	.99950
	3.4	.99966	.99968	.99969	.99970	.99971	.99972	.99973	.99962	.99964	.99965
	3.5	.99977	.99978	.99978	.99979	.999980	.99981	.99973	.99974	.99975	.99976
	3.6	.99984	.99985	.99985	.99986	.99986	.99987	.99981	.99982	.99983	.99983
	3.7	.99989	.99990	.99990	.99990	.99991	.99991	.999987	.99988	.99988	-99989
	3.8	.99993	.99993	.99993	.99994	.99994	.99994	.99992	.99992 .99995	.99992	.99992
_	3.9	.99995	.99995	.999%	.99996	.999966	.99996	.99996		.99995	.99995
							00000	177750	.99996	.99997	.99997